# FF-L Series Mulcher

Mini Excavator Forestry Mulcher 2t – 5t Carrier





The FF-L forestry mulcher, engineered for 2-5 ton excavators, excels in shredding material up to 5" diameter. Its advanced Bite Limiter technology is optimized for high-efficiency vegetation management, offering exceptional reliability, efficient shredding, and ease of maintenance. The FF-L features a Direct Drive motor, which not only reduces maintenance but also enables a remarkably compact machine design. Additionally, the FF-L can be fitted with Planer blades and Carbide teeth, further enhancing its versatility and performance.

FFL Series

Developed and Build in Italy for the North American Market



## FF - L Mini Excavator Series Mulcher

## FF -L 55 & 75

## 7 - 24 Gpm

#### STANDARD EQUIPMENT

- Casappa Gr 3 Gear Motor
- Flow management valve
- NO Case drain required
- Bite limiter technology
- 2.5m hoses
- Double Planer teeth
- Replaceable Skids
- Base plate

#### **Optional**

- Fixed Piston motor
- Carbide teeth
- Stump Splitter teeth
- Single Planer teeth





FLOW CONTROL VALVE, PAIRED WITH CASAPPA GEAR MOTOR OR FIXED PISTON MOTOR AND FLUID BOX



Flow Control Valve for a complete and safe engine management with relief valve, anticavitation system. E flow regulation for Rotor RPM

Double Planer Planer carbide Carbide

Rock Carbide










MODEL	FF-L55	FF-L 75
CUTTING WIDTH (inch/metric)	22/56	30/76
WEIGHT (Lbs./Kg)	376/170	443/200
OIL PRESSURE (bar) 1Bar = 14.5psi	220-250	220-250
OIL FLOW (I/min) 1Gpm = 3.78L	30 - 90	40 - 90
NUMBER OF TOOLS	12	16
MAX CUTTING DIAMETER (inch/metric)	5/12	5/12
DIMENSION A (mm)	22/56	30/76
DIMENSION B (mm)	36/930	44/1130





Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice