### MINI SKID STEER FORESTRY MULCHER F2-S90 & F2-S115

Variable Torque









The VT (Variable Torque) piston engine improves mulcher efficiency by automatically increasing torque during demanding tasks, providing an extra power boost to prevent rotor stalling. This system ensures the mulcher consistently operates at the optimal torque level, delivering top performance while conserving fuel


Performance/Counter knife Hardox Wear parts



Bite Limiter Standard



Excavator mounting plate



#### Max operating height 45 inches above ground !!!



Bungee cord secured hoses

Bolted Stub Shaft



### Technical Specification F2 - S 90 & 115 Variable Torque

Model	lbs	Flow Gpm	Psi	Width Inch	Tool #	Motor ccm	Drive line
F2-SSK 90	907	12-27	3000 4500	35 work 43 outer	26	VM 22- 45	3 Belts
F2-SSk 115	973	12 -27	3000 4000	45 work 54 outer	34	VM 22- 45	3 Belts

# FERNTREE EQUIPMENT & DISTRIBUTION

## Import & Distribution North-America

Info@ferntree.ca +1 778 222 9111 Guelph Ontario Canada

### **Standard Equipment**

- ➤ Hydraulic Flat Face Coupler
- ➤ 22-45cc Variable Motor (VT)
- Carbide tooth
- Belt transmission
- > Rear Chain Guard
- Adjustable Skids
- ➤ 3F Ferntree Multifunctional Valve (Bypass, anti-shock, oil flow diverter)
- Push Bar
- ➤ Bite Limiter / Depth Control Rotor
- Excavator base Plate for DUAL USE up to 8t carrier.

### **Optional Equipment**

- > ASV 40 Mount Plate
- > AVANT MOUNT Plate
- Specific Excavator mount
- > Planer Teeth
- > Double tip carbide